





Lighthouse proprietary M4 technology ensuring it delivers sponsor message and advertising in accurate color. In addition, the high brightness and wide viewing angle make sure it could reach maximum crowd.

The Fv OVAL series could be front access or top access , offering different options for easy service.

Lighthouse Fv Oval series offers a cost-effective solution without compromising on performance and reliability.

Fv Oval


16mm / 20mm Permanent Outdoor Front Access / **Top Access Oval LED** Fascia

Outdoor & Sports Arenas


Fv Oval

Configurations





1.28m (4.19ft.) x 0.96m (3.15ft)



Input source



	Fv	16i/o-OVAL-FA/TA	Fv20i/o-OVAL-FA/T/		
to wisting	•		6,000		
Visual Characteristics	nits	160 (+80 / 870)			
Brightness	deg.				
Viewing Angle - Horizontal (50% brightness)	deg.	60	60 (+25 / -35)		
Viewing Angle - Vertical (50% brightness)	9		1,1,1		
	R/G/B	16.0	20.0		
Pixel Configuration	mm		16		
Pixel Pitch	bit				
Processing Depth			4:3		
Modular Characteristics					
Aspect Ratio	/ ft		1280 / 4.2		
	mm / ft	9	960 / 3.15		
Panel Width	mm / ft	1.2	23 / 13.24		
Panel Height	sq.m / sq.ft	2060	64 x 48		
Panel Surface Area	wxh	80 x 60			
Pixel Resolution					
Environmental	ID.	IP65 / IP43			
Ingress Protection (Front / Rear)	IP	>	≥100,000		
	hrs				
Lifetime (50% brightness)	ocifications without no	otice.			

^{*} Lighthouse reserves the right to change any specifications without notice.